









Webbing Slings

2150 - Polyester Webbing Slings





Webbing slings are available from 25mm to 300mm width & 500kg to 24,000kg capacity, although higher capacity slings can be made as per requirement. Additional to becket eyes (soft), reverse, flat & leather protected eyes are available. Moreover wear sleeves can be fitted as per customer requirement. EN 1492 standard is used during manufacturing, inspection and testing of all our webbing fittings slings. Safety factor of 7:1 (excl. when fitted with steel end fittings where it is 4:1) Certification provided with all webbing slings products and flat woven webbing slings (polyester) with soft eyes also available.





Single Ply Flat Polyester Webbing Sling							
				100%	200%	140%	80%
							
Part No.	Colour	Width		SWL (Kg) in different angle modes			
		Inch	mm				
SPSL.0025	Violet	1	25	500	1000	700	400
SPSL.0050	Green	2	50	1000	2000	1400	800
SPSL.0075	Yellow	3	75	1500	3000	2100	1200
SPSL.0100	Grey	4	100	2000	4000	2800	1600
SPSL.0125	Red	5	125	2500	5000	3500	2000
SPSL.0150	Brown	6	150	3000	6000	4200	2400
SPSL.0200	Blue	8	200	4000	8000	5600	3200
SPSL.0250	Orange	10	250	5000	10000	7000	4000
SPSL.0300	Orange	12	300	6000	12000	8400	4800

Double Ply Flat Polyester Webbing Sling							
				100%	200%	140%	80%
							
Part No.	Colour	Width		SWL (Kg) in different angle modes			
		Inch	mm				
DPSL.0025	Violet	1	25	1000	2000	1400	800
DPSL.0050	Green	2	50	2000	4000	2800	1600
DPSL.0075	Yellow	3	75	3000	6000	4200	2400
DPSL.0100	Grey	4	100	4000	8000	5600	3200
DPSL.0125	Red	5	125	5000	10000	7000	4000
DPSL.0150	Brown	6	150	6000	12000	8400	4800
DPSL.0200	Blue	8	200	8000	16000	11200	6400
DPSL.0250	Orange	10	250	10000	20000	14000	8000
DPSL.0300	Orange	12	300	12000	24000	16800	9600

Webbing Slings

2150 - Polyester Webbing Slings

Three Ply Flat Polyester Webbing Sling							
				100%	200%	140%	80%
							
Part No.	Colour	Width		SWL (Kg) in different angle modes			
		Inch	mm				
TPSL.0025	Violet	1	25	1500	3000	2100	1200
TPSL.0050	Green	2	50	3000	6000	4200	2400
TPSL.0075	Yellow	3	75	4500	9000	6300	3600
TPSL.0100	Grey	4	100	6000	12000	8400	4800
TPSL.0125	Red	5	125	7500	15000	10500	6000
TPSL.0150	Brown	6	150	9000	18000	12600	7200
TPSL.0200	Blue	8	200	12000	24000	16800	9600
TPSL.0250	Orange	10	250	15000	30000	21000	12000
TPSL.0300	Orange	12	300	18000	36000	25200	14400

Four Ply Flat Polyester Webbing Sling							
				100%	200%	140%	80%
							
Part No.	Colour	Width		SWL (Kg) in different angle modes			
		Inch	mm				
FPSL.0025	Violet	1	25	2000	4000	2800	1600
FPSL.0050	Green	2	50	4000	8000	5600	3200
FPSL.0075	Yellow	3	75	6000	12000	8400	4800
FPSL.0100	Grey	4	100	8000	16000	11200	6400
FPSL.0125	Red	5	125	10000	20000	14000	8000
FPSL.0150	Brown	6	150	12000	24000	16800	9600
FPSL.0200	Blue	8	200	16000	32000	22400	12800
FPSL.0250	Orange	10	250	20000	40000	28000	16000
FPSL.0300	Orange	12	300	24000	48000	33600	19200

