

Wire Rope Slings and Fittings

W 400 - Three & Four Legs Steel Wire Rope Sling



C/W Nut & Bolt Shackle



C/W Eye Hook with Safety Latch

Three & Four Leg Steel Wire Rope Sling			
Part No.	Dia		SWL (0 - 45°) Sling angle to vertical
	mm	inch	
W400.006	6	1/4	1.0
W400.008	8	5/16	1.7
W400.010	10	3/8	2.7
W400.012	12	15/32	3.8
W400.013	13	1/2	4.4
W400.014	14	35/64	5.2
W400.016	16	5/8	6.9
W400.018	18	45/64	8.6
W400.019	19	3/4	9.7
W400.020	20	25/32	10.7
W400.022	22	7/8	13.0
W400.024	24	15/16	15.5
W400.026	26	1	18.0
W400.028	28	1.1/8	21.0
W400.032	32	1.1/4	27.5
W400.036	36	1.3/8	34.8
W400.038	38	1.1/2	38.9
W400.040	40	1.7/12	43.2
W400.044	44	1.3/4	52.0
W400.052	52	2	72.9
W400.056	56	2.1/4	84.2
W400.060	60	2.23/64	96.6
W400.064	64	2.1/2	113.8
W400.071	71	2.51/64	136.1
W400.076	76	3	160.0
W400.089	89	3. 1/2	216.9